

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SYNERGY MFG. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SYNERGY MFG IS PROHIBITED.

Revisions			
Rev.	Description	Date	Approved
A	Initial Release Per ECO 20-001	1/3/20	A.S.



Jeep Wrangler Adjustable Rear Upper Control Arms

Installation Instructions

Applications:
2007-2018 Jeep Wrangler (JK/JKU)
2018+ Jeep Wrangler (JL/JLU)



TITLE:
**JEEP JK/JL ADJ REAR UPPER CONTROL
ARM INSTALLATION INSTRUCTIONS**

SIZE	DWG NO:	REV
A	8854-01-INST	A
	SCALE: N/A	PAGE 1 OF 4



JEEP JK/JL ADJ REAR UPPER CONTROL ARM INSTALLATION INSTRUCTIONS

Thank you for purchasing the best aftermarket products available for your vehicle. We strongly feel that the parts you are about to install should meet or exceed your expectations for performance. Proper assembly is critical to the performance of these components and the vehicle as a whole. Please take the time to carefully read these instructions and familiarize yourself with the installation procedure before working on your vehicle. If you have any questions PLEASE contact Synergy Manufacturing BEFORE beginning installation. Thanks again for supporting Synergy – enjoy the performance benefits of the best aftermarket products available for your vehicle!

Synergy Manufacturing

Phone: (805) 242-0397

Email: support@synergymfg.com

Modifying or otherwise altering vehicle components may cause the vehicle to handle differently than originally designed. It is the driver’s responsibility to familiarize themselves with the performance and handling characteristics of the modified vehicle. Vehicles with larger diameter than stock tires must be driven carefully and cannot be expected to perform as stock or meet OEM performance with regard to handling, braking or crash performance. Ensure all replacement components are compatible with vehicle capacities so as not to overload components, especially tires. It is up to the individual to ensure that the vehicle and all components are compatible with the intended vehicle use, including load ratings, road conditions, and driver abilities. Thorough and frequent vehicle inspections are recommended to ensure a safe and reliable state of readiness, especially after off-highway use.

PARTS LIST

8854-01 Jeep Wrangler Adjustable Rear Upper Control Arms		
QTY	Part Number	Description
1	885401-L	JK/JL RUCA LEFT FINAL ASSEMBLY
1	88 5401-R	JK/JL RUCA RIGHT FINAL ASSEMBLY

GENERAL NOTES

- These instructions are also available on our website; www.synergymfg.com. Check the website before you begin for any updated instructions and additional photos for your reference.
- These control arms are a direct replacement for the stock control arms. They are compatible with stock and lifted Jeeps.
- The installation of these control arms will allow the rear axle position and pinion angle to be adjusted in order to accommodate lift springs, aftermarket driveshafts, or larger tires.
- These control arms feature Synergy Dual Durometer Bushings which are free-floating Teflon lined bushings that require no grease or other maintenance. Replacement bushings are available at www.synergymfg.com.
- These control arms are 17.375” collapsed and 18.875” extended.

TOOLS REQUIRED

- 19mm (or 3/4"), 21mm, and 22mm Sockets and Wrenches
- 1 1/4" Open End Wrench (Or Large Crescent Type Wrench)
- Tape Measure
- Torque Wrench
- Jack and Jack Stands

ESTIMATED INSTALLATION TIME

1 Hour

INSTALLATION

1. Park the vehicle on a flat, level surface. Put the vehicle in gear or in park and set the parking brake. Raise the vehicle up and support the frame with jack stands or on a lift. We recommend removing the rear wheels (22mm or 19mm socket) in order to ease installation.
2. Remove one of the rear upper control arms. The bolts are a 21mm head and both the frame side and axle side use a 'flag' nut, so no wrench is necessary to prevent the nut from spinning. It may be necessary to remove rear bump stop spacers to remove the axle side bolt.
3. Install a new Synergy Adjustable control arm. The arms install with the pinch bolts down and the fixed end of the arm on the frame side. The bend in the arm goes in towards the frame for tire clearance. Adjust the length as necessary by rotating the silver double adjuster sleeve with a 1 1/4" open end wrench or Crescent style adjustable wrench. Once the bolt holes line up, re-install the factory hardware. See **Figures 1 and 2**.



Figures 1 and 2. Driver Side Synergy Rear Upper Control Arm



- Repeat steps 2 and 3 for the other side of the vehicle.
- Torque frame side hardware to 120 lb-ft. Torque axle side hardware to 95 lb-ft. Leave pinch bolts loose at this point.
- Re-install wheels and torque lug nuts (See **Table 1**). Place vehicle back on ground at ride height.
- With the vehicle back on the ground, adjust the control arm lengths to set the axle in the correct position, and set the correct pinion angle for the driveshaft being used. On JL applications, we recommend keeping the upper control arms as short as possible, and using the lower control arms to set pinion angle. See **Tables 2 and 3**.
- Double check control arm lengths to make sure they are identical side to side. After checking, torque pinch bolts to 90 lb-ft.
- If the pinion angle has changed significantly from stock (pinion is higher than stock) then we recommend over-filling the rear differential by a quart or so in order to ensure the pinion is getting sufficient oiling. Aftermarket diff covers often have raised fill plugs to accomplish this, otherwise you can add the extra fluid through the vent tube.

Installation is Complete

Table 1. Jeep JK/JL Bolt Torques

Bolted Joint Location	Wrench Size	Torque
JL Lug Nuts	22mm	125 lb-ft
JK Lug Nuts	19mm	95 lb-ft
Rear Upper Control Arm to Frame	21mm	120 lb-ft
Rear Upper Control Arm to Axle	21mm	95 lb-ft
Synergy MFG Control Arm Pinch Bolts	19mm	90 lb-ft

**Table 2. Jeep JK Recommended Control Arm Lengths
(For 3-4.5" of Lift)**

Vehicle Type	UCA Length	LCA Length
4 Door with CV Driveshaft	18.25"	20.25"
2 Door with CV Driveshaft	18.75"	20.25"

**Table 3. Jeep JL Recommended Control Arm Lengths
(For 2-3" Of Lift)**

Vehicle Type	UCA Length	LCA Length
4 Door	17.375"	20"
2 Door	17.375"	19.75"