

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SYNERGY MFG. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SYNERGY MFG IS PROHIBITED.


Revisions			
Rev.	Description	Date	Approved
A	Initial Release Per ECO 18-136	12/5/18	KB
B	Revised Per ECO 19-104	8/19/19	A.S.



Jeep Wrangler Rear Adjustable Track Bar

Installation Instructions

Applications:
2018+ Jeep Wrangler (JL)



TITLE:
JEEP WRANGLER JL REAR ADJ TRACK BAR INSTALLATION INSTRUCTIONS

SIZE	DWG NO:	REV
A	8862-01-INST	B
	SCALE: N/A	PAGE 1 OF 6



JEEP WRANGLER JL REAR ADJ TRACK BAR INSTALLATION INSTRUCTIONS

Thank you for purchasing the best aftermarket products available for your vehicle. We strongly feel that the parts you are about to install should meet or exceed your expectations for performance. Proper assembly is critical to the performance of these components and the vehicle as a whole. Please take the time to carefully read these instructions and familiarize yourself with the installation procedure before working on your vehicle. If you have any questions PLEASE contact Synergy Manufacturing BEFORE beginning installation. Thanks again for supporting Synergy – enjoy the performance benefits of the best aftermarket products available for your vehicle!

Synergy Manufacturing
Phone: (805) 242-0397
Email: support@synergymfg.com

Modifying or otherwise altering vehicle components may cause the vehicle to handle differently than originally designed. It is the driver’s responsibility to familiarize themselves with the performance and handling characteristics of the modified vehicle. Vehicles with larger diameter than stock tires must be driven carefully and cannot be expected to perform as stock or meet OEM performance with regard to handling, braking or crash performance. Ensure all replacement components are compatible with vehicle capacities so as not to overload components, especially tires. It is up to the individual to ensure that the vehicle and all components are compatible with the intended vehicle use, including load ratings, road conditions, and driver abilities. Thorough and frequent vehicle inspections are recommended to ensure a safe and reliable state of readiness, especially after off-highway use.

PARTS LIST

8862-01 Jeep Wrangler JL Rear Track Bar		
QTY	Part Number	Description
1	886201-PC	JEEP JL REAR ADJ TRACK BAR, POWDERCOATED
1	3622-07-14L-PL	DOUBLE ADJUSTER SLEEVE 7/8 – 14TPI LH
1	4811-01	TRACK BAR DDB JOINT, 1.75OD BUSHING, 7/8-14LH SHANK
1	4327-01	TRACK BAR BUSHING, 1.75OD .563 BOLT
1	N/A	1/2-20 X 1 3/4” HEX BOLT, GRADE 8
1	N/A	1/2-20 TOP LOCK NUT

GENERAL NOTES

- These instructions are also available on our website; www.synergymfg.com. Check the website before you begin for any updated instructions and additional photos or videos for your reference.
- The installation of this adjustable track bar will allow you to correctly align the rear axle after a suspension lift kit is installed.
- The track bar features a double adjuster sleeve which allows you to adjust the length of the track bar without removing the end of the track bar from the vehicle.
- Replacement bushings are available from Synergy Mfg.

TOOLS REQUIRED


- 21mm and 3/4 inch sockets and wrenches
- 1 1/4 inch wrench or adjustable (Crescent type) wrench
- Torque Wrench
- Tape measure and straight edge

ESTIMATED INSTALLATION TIME

1/2 Hour

INSTALLATION

1. Installation can be done on the ground. There is no need to lift the vehicle off the ground or remove the wheels and tires. The track bar comes preassembled with all necessary components.
2. Using a 21mm socket, loosen and unbolt the rear track bar from the axle side mount. Support the track bar so it will not fall when you remove the bolt. Save the stock hardware, it will be re-used. See **Figures 1 and 2**.



Figures 1 and 2. Removing the Track Bar from the Axle End

3. Using a 21mm socket, loosen, then unbolt the frame side track bar bolt taking care to once again support the track bar before you pull the bolt all the way out. Save the stock hardware, it will be re-used. Completely remove the track bar. See **Figure 3**.




Figure 3. Removing the Track Bar from the Frame Side

4. Install the Synergy Mfg track bar by putting the adjustable side in the frame side track bar mount and reuse the OEM bolt and nut. Make sure the bend in the bar and the pinch bolt bungs face down. See **Figure 4**.



Figure 4. Installing the Synergy Mfg Track Bar at the Frame

- Next, install the non-adjustable side into the axle side mount. Adjust the track bar length with the adjuster sleeve at the frame end until the track bar bushing bolt hole and the axle mount bolt holes line up. Make sure the adjuster sleeve end is adjusted by turning the adjuster sleeve and not the bushing end or track bar itself. The bend in the tube should point down and the pinch bolt mount on the other end should also point down when done. See **Figures 5 and 6**. If the bar cannot be adjusted to make the bolt holes line up, a ratchet strap between the frame and opposing side on the axle can be used to pull the body whichever way it needs to get the bolts to line up.

BEND IN TRACK BAR GOES DOWN



Figure 5. Installing the Synergy Mfg Track Bar at the Axle



Figure 6. Correctly Installed Synergy Mfg Rear Track Bar

- Torque the track bar bolts to OEM specifications; Axle side bolt and nut – 89 lb-ft, frame side bolt and nut – 92 lb-ft.
- With the Jeep on the ground at ride height, use the double adjuster to center the axle under the body of the Jeep. You can measure from the frame to the tire on each side to get the axle centered. Make sure the adjuster sleeve end is adjusted by turning the adjuster sleeve and not the bushing end or track bar itself. We recommend rotating the sleeve until one of the slots in the sleeve lines up with the slot in the track bar. See **Figure 7**.



Figure 7. Adjusting the Track Bar to Center the Axle

8. With a 3/4 inch socket and wrench, tighten the pinch bolt at the double adjuster on the track bar to 90 lb-ft. See **Figure 8**.



Figure 8. Tightening the Pinch Bolt and Nut

9. Re-check bolt torques after the first 100 miles and again after each off-road trip.

Installation is Complete

Table 1. Jeep JL Rear Track Bar Bolt Torques

Bolted Joint Location	Wrench Size	Torque
Axle Side Track Bar Bolt	21mm	89 lb-ft
Frame Side Track Bar Bolt	21mm	92 lb-ft
Adjuster Pinch Bolt	3/4"	90 lb-ft